


Kod: 200098 EAN: 5905378200098

LED line PRIME LED strip 480 COB 24V 2700K 18W 30m



LED Strip line is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.



The colour temperature range of the product falls within 3 steps of MacAdam formula, which ensures high consistency of the produced light.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



Cutting section



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



LED type



Lifespan



Laminate (thickness)



LED quantity



LED quantity (1m)

Parametr	Wartość
Luminous efficacy	100 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	F
Colour consistency in MacAdam ellipses	≤3
IP protection rating	IP20
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Minimum purchase quantity	30
Lifetime L70B50	50 000
Wire length	200 mm
Current (1m)	0,75
Colour rendering index Ra	90
Metres per roll	30 m

Parametr	Wartość
Type of adhesive tape	3M 300 LSE
Colour consistency in MacAdam ellipses	≤3
Ambient temperature suitable for operation	-30÷45 °C
For indoor use	Inside
IEC protection class	III
Length	30000 mm
Width	10 mm
Height	2 mm
Form of the product (EPREL)	0.46 0.411
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes

The lumen maintenance factor	96 %
Beam angle	180 °
LED type	COB
LED quantity	2400
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	2400
Cutting section	5

Mains or non- mains light source (EPREL)	NMLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
Total luminous flux (EPREL)	900
On-mode power Pon (EPREL)	9
Useful luminous flux Φ_{use} (EPREL)	900
Beam angle in degrees (EPREL)	180
Power	<ul style="list-style-type: none">18 W / m
Voltage	<ul style="list-style-type: none">24 V DC
Correlated colour temperature	<ul style="list-style-type: none">2700 K

Opakowanie jednostkowe



Width	380 mm
Height	130 mm
Length	400 mm
Weight	0,71 kg
	30

Opakowanie zbiorcze



Number of pieces/tape in meters pack zb	20 szt.
Width	450 mm
Height of collective packaging	290 mm
Length	350 mm
Weight	14,1 kg
Volume	0,045 m3

Europaleta



Number of pieces/tapes in meters euro pallet	14400 m
Quantity collective euro pallet	480 szt.
Weight of a euro pallet	278,8
Pallet height	1740 mm
Quantity in 1 layer	80 szt.
Number of layers	6