

LED line LITE


Code: 209824

EAN: 5905378209824

Park luminaire PARKLITE 3CCT(3/4/6K)
50-80-100W 6000-12000lm IP65 grey
LITE



PARKLITE park mount from LED line LITE is a modern lighting solution, available in power 50W, 80W and 100W. Its total luminous flux ranges from 6000 to 12,000 lumens, providing effective lighting. The housing is characterized by a high PF power factor of 0.9 and a L70B50 durability of 25,000 hours. The aluminum and tempered glass housing material provides robustness and resistance to damage (IP65, IK08).



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 50 W • 80 W • 100 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 6000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	120
Luminous flux	6000-12000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
ULOR	2,3 %
Wire length	400 mm
Frequency of the supply voltage	50/60Hz
Beam angle	100
LED type	SMD LED 2835
LED quantity	384
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-30÷50
Height	117
Weight	2190
Colour	209824
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 209824


EAN: 5905378209824

Park luminaire PARKLITE 3CCT(3/4/6K)
50-80-100W 6000-12000lm IP65 grey
LITE


Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	420 mm
Height	135 mm
Length	425 mm
Weight	2,25 kg



Bulk packaging

Quantity	4
Width	445 mm
Height	430 mm
Length	550 mm
Volume	0,105 m3
Weight	9,3 kg



Europallet

Height	1780 mm
Quantity in layer	8
Number of layers	4
Bulk quantity	32
Weight	74,4 kg

LED line LITE

Code: 209824

EAN: 5905378209824

**Park luminaire PARKLITE 3CCT(3/4/6K)
50-80-100W 6000-12000lm IP65 grey
LITE**

Example application