


LED line LITE Code: 209923 EAN: 5905378209923

## DOWNLIGHT EASY FLEX 4000K 6W 450lm round IP20 White LITE





Downlight EASY FLEX 6W is a modern lighting luminaire with a neutral colour of light 4000 K, emitting a luminous flux of 450 lm. It is characterized by a round shape and a ratio of Ra color reproduction at level 80. At 6 W power, its luminous efficiency is 75 lm/W. The housing has IP20 leak class and IK05 load capacity, which provides adequate protection against damage.

















#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 6 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	75
Luminous flux	450
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	28
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	`-20 ÷ 40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-102
Height	17
Fixture's diameter	140
Weight	0,152 kg
Colour	White




LED line LITE Code: 209923 EAN: 5905378209923

# DOWNLIGHT EASY FLEX 4000K 6W 450lm round IP20 White LITE

## **Technical drawing**



## **Light distribution**



## Additional product photos












## Logistics data







### Single packaging

Width	31 mm
Height	155 mm
Length	160 mm
Weight	0,16 kg

## Bulk packaging

Quantity	40
Width	335 mm
Height	335 mm
Length	340 mm
Weight	8,94 kg

### Europallet

Height	
Bulk quantity	960

## MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 209923 EAN: 5905378209923

# DOWNLIGHT EASY FLEX 4000K 6W 450lm round IP20 White LITE

**Example application**