

LED line LITE


Code: 209923

EAN: 5905378209923

**DOWNLIGHT EASY FLEX 4000K 6W
450lm round IP20 White LITE**



Downlight EASY FLEX 6W is a modern lighting luminaire with a neutral colour of light 4000 K, emitting a luminous flux of 450 lm. It is characterized by a round shape and a ratio of Ra color reproduction at level 80. At 6 W power, its luminous efficiency is 75 lm/W. The housing has IP20 leak class and IK05 load capacity, which provides adequate protection against damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 6 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	75
Luminous flux	450
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	28
Power Factor	≥0,9
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20 ÷ 40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-102
Height	17 mm
Fixture's diameter	140 mm
Weight	0,16 kg
Colour	White


LED line LITE

Code: 209923


EAN: 5905378209923

**DOWNLIGHT EASY FLEX 4000K 6W
450lm round IP20 White LITE**

Technical drawing





Light distribution



Additional product photos



Logistics data



Single packaging

Width	31 mm
Height	155 mm
Length	160 mm
Weight	0,22 kg

Bulk packaging

Quantity	40
Width	335 mm
Height	335 mm
Length	340 mm
Weight	8,94 kg

Europallet

Quantity	960
Height	1,7 m
Bulk quantity	24
Weight	300 kg

LED line LITE

Code: 209923

EAN: 5905378209923

**DOWNLIGHT EASY FLEX 4000K 6W
450lm round IP20 White LITE**

Example application