LED line LITE

Code: 209930

EAN: 5905378209930

DOWNLIGHT EASY FLEX 4000K 12W 900lm round IP20 White LITE

Downlight EASY FLEX 12W 4000K from LED line LITE is a modern lighting with high performance. It emits a 900 lumen light stream, providing optimal brightness with minimal energy consumption of 12 W. The angle of light distribution of 120° allows effective illumination of the space. Equipped with SMD2835 diode technology, it guarantees a durability of up to 30,000 hours and Ra color reproduction factor of 80, which affects the naturalness of color perception.

3 WARRANTY | IP 20 | IK 05 | PF 0,9 | 220-240V AC | MAX -20÷40°C | CE

Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 12 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	75
Luminous flux	900
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	42
Power Factor	>=0,9
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-130
Height	17 mm
Fixture's diameter	170 mm
Weight	0,24 kg
Colour	White

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**


LED line LITE

Code: 209930


EAN: 5905378209930

DOWNLIGHT EASY FLEX 4000K 12W 900lm round IP20 White LITE

Technical drawing



Light distribution




Additional product photos








Logistics data




Single packaging

Width	31 mm
Height	175 mm
Length	175 mm
Weight	0,29 kg



Bulk packaging

Quantity	40
Width	365 mm
Height	335 mm
Length	370 mm
Weight	13,08 kg



Europallet

Quantity	960
Height	1,9 m
Bulk quantity	24
Weight	370 kg

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line LITE

Code: 209930

EAN: 5905378209930

DOWNLIGHT EASY FLEX 4000K 12W 900lm round IP20 White LITE

Example application

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**