

LED line LITE

Code: 209954

EAN: 5905378209954

**DL DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)  
9/12/15W 1050lm round IP20 black LITE**


The round downlight EASY FLEX 9-12-15W CCT with a power of 1050 lm is characterized by its versatility thanks to the choice of three colour temperatures: 3000 K, 4000 K and 5000 K, which allows to adjust lighting to different needs. It has an E energy class and a Ra colour reproduction factor of 80, which ensures good light quality.


**Technical data**






| Parameter                         | Value  |
|-----------------------------------|--|
| Energy efficiency class 2019/2015 | E  |
| Warranty                          | 3  |
| Power                             | <ul style="list-style-type: none"> <li>• 9 W</li> <li>• 12 W</li> <li>• 15 W</li> </ul>        |
| Voltage                           | <ul style="list-style-type: none"> <li>• 220-240 V AC</li> </ul>                               |
| Correlated colour temperature     | <ul style="list-style-type: none"> <li>• 3000 K</li> <li>• 4000 K</li> <li>• 5000 K</li> </ul> |
| Colour rendering index Ra         | 80   |
| IP protection rating              | IP20   |
| IK protection rating              | 05   |
| IEC protection class              | II   |
| Luminous efficacy                 | 70   |
| Luminous flux                     | 1050   |
| The lumen maintenance factor      | 96   |
| Lifetime L70B50                   | 30 000 h   |
| Survival factor                   | 0.9  |

| Parameter                                  | Value  |
|--|--|
| Colour consistency in McAdam ellipses      | ≤6   |
| Frequency of the supply voltage            | 50/60Hz  |
| Beam angle                                 | 120  |
| LED type                                   | SMD2835  |
| LED quantity                               | 84   |
| Number of on/off cycles                    | 15000  |
| Lamp's warm-up time to 60%                 | 1  |
| Ambient temperature suitable for operation | -20÷40   |
| Installation method                        | 3in1 surface mounted, flush mounted, suspended |
| Mounting hole diameter                     | 65-130   |
| Height                                     | 17   |
| Fixture's diameter                         | 170  |
| Weight                                     | 0,24 kg  |
| Colour                                     | Black  |

LED line LITE

Code: 209954

EAN: 5905378209954

**DL DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)  
9/12/15W 1050lm round IP20 black LITE****Technical drawing****Light distribution****Additional product photos****Logistics data****Single packaging**

|        |          |
|--------|----------|
| Width  | 31 mm    |
| Height | 175 mm   |
| Length | 175 mm   |
| Weight | 0,215 kg |

**Bulk packaging**

|          |          |
|----------|----------|
| Quantity | 40       |
| Width    | 365 mm   |
| Height   | 335 mm   |
| Length   | 370 mm   |
| Weight   | 13,08 kg |

**Europallet**

|               |     |
|---------------|-----|
| Bulk quantity | 960 |
|---------------|-----|

**MORE EFFICIENCY FOR THE LED WORLD**

**LED line**

---

LED line LITE

Code: 209954

EAN: 5905378209954

**DL DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)  
9/12/15W 1050lm round IP20 black LITE**

---

**Example application**