


LED line LITE Code: 209978 EAN: 5905378209978

### LED line LITE Downlight EASY FLEX 18W CCT 1530lm round white with motion sensor





New

Downlight EASY FLEX 18W CCT is a modern lighting setting, characterized by an elegant round shape and white finish. It emits a total luminous flux of 1530 lm at 85 lm/W. Thanks to the function of changing the temperature of light (3000 K, 4000 K, 5000 K) it provides flexibility to adjust the atmosphere to the needs of the user.

















#### **Technical data**

Parameter	Value	
Energy efficiency class 2019/2015	E	
Warranty	3	
Power	• 18 W	
Voltage	• 220-240 V AC	
Correlated colour temperature	• 3000 K • 4000 K • 5000 K	
Colour rendering index Ra	80	
IP protection rating	IP20	
IK protection rating	05	
IEC protection class	II	
Luminous efficacy	85	
Luminous flux	1530 96 30 000 h	
The lumen maintenance factor		
Lifetime L70B50		
Survival factor	0.9	

Parameter	Value	
Colour consistency in McAdam ellipses	≤6	
Frequency of the supply voltage	50/60Hz	
Fixture's diameter	225	
Beam angle	120	
LED type	SMD2835	
LED quantity	86	
Number of on/off cycles	15000	
Lamp's warm-up time to 60%	1s	
Ambient temperature suitable for operation	`-20 ÷ 40	
Installation method	3in1 surface mounted, flush mounted, suspended	
Mounting hole diameter	65-180	
Height	17	
Weight	360	
Colour	White	



LED line LITE Code: 209978 EAN: 5905378209978


# LED line LITE Downlight EASY FLEX 18W CCT 1530lm round white with motion sensor

#### **Technical drawing**



#### Light distribution

#### Luminous [cd/klm]



#### Additional product photos












#### Logistics data







#### Single packaging

Width	31 mm	
Height	230 mm	
Length	230 mm	
Weight	0,36 kg	

#### **Bulk packaging**

Quantity	20
Width	335 mm
Height	255 mm
Length	480 mm
Weight	9,52 kg

#### Europallet

Bulk quantity	480

### MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 209978 EAN: 5905378209978

## LED line LITE Downlight EASY FLEX 18W CCT 1530lm round white with motion sensor

**Example application**