

LED line LITE

Code: 209985

EAN: 5905378209985

LED line LITE Downlight EASY FLEX  
24W 4000K 2110lm round white



Downlight EASY FLEX 24W 4000K is a modern LED lighting with high performance and elegant round shape. It emits a luminous flux of 2110 lumens at a colour temperature of 4000 K, which provides neutral light ideal for different spaces. The product achieves a colour reproduction coefficient of Ra at level 80 and energy efficiency E. It is impact resistant (IK05) and has IP20 leak class.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 24 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	88
Luminous flux	2110
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	300
Beam angle	120
LED type	SMD2835
LED quantity	84
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	` -20 ÷ 40
Mounting hole diameter	65-240
Height	17
Weight	0,36 kg
Colour	White


LED line LITE

Code: 209985


EAN: 5905378209985

LED line LITE Downlight EASY FLEX  
24W 4000K 2110lm round white

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	31 mm
Height	305 mm
Length	305 mm
Weight	0,55 kg



Bulk packaging

Quantity	10
Width	325 mm
Height	325 mm
Length	335 mm
Weight	8,42 kg



Europallet

Bulk quantity	240
---------------	-----

---

LED line LITE

Code: 209985

EAN: 5905378209985

**LED line LITE Downlight EASY FLEX  
24W 4000K 2110lm round white**

---

**Example application**