

LED line LITE Code: 210028 EAN: 5905378210028

DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K) 45W 4050lm round IP20 White LITE





Downlight EASY FLEX 45W CCT is a modern lighting fixture from the LED line LITE brand, characterized by a luminous flux efficiency of 2110 lumens. It allows for the selection of color temperature in the range of 3000 K, 4000 K, and 5000 K, providing flexibility in space arrangement. The IP20 protection class guarantees protection against solid bodies larger than 12 mm, while the IK05 protection rating ensures resistance to impacts.

















Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 45 W
Voltage	• 220-240 V AC
Correlated colour temperature	3000 K4000 K5000 K
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	90
Luminous flux	4050
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Colour consistency in McAdam ellipses	≤6


Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	500
Beam angle	120
LED type	SMD2835
LED quantity	168
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-240
Height	17
Weight	2,05
Colour	White




LED line LITE Code: 210028 EAN: 5905378210028

DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K) 45W 4050lm round IP20 White LITE

Technical drawing






Additional product photos









Logistics data







Single packaging

Width	35 mm
Height	505 mm
Length	505 mm
Weight	2,05 kg

Bulk packaging

Quantity	10
Width	520 mm
Height	375 mm
Length	525 mm
Weight	20,50 kg

Europallet

Bulk quantity

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 210028 EAN: 5905378210028

DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K) 45W 4050lm round IP20 White LITE

Example application