

LED line PRIME Code: 210486 EAN: 5905378210486

Track light LUMICANTO 14-29W CCT 36/60° black PRIME





Track light LUMICAANTO 14-29W CCT 36/60° in black is an advanced LED line PRIME lighting setting that is characterized by high energy efficiency. Thanks to the BRIDGELUX COB LED technology and the Ra colour reproduction factor of 90, it provides clear and natural colours. The light angle of 36/60° allows precise light flow control.



















Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 14-29 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 6000 K
Colour of the light	White
Colour rendering index Ra	90
IP protection rating	IP20
IK protection rating	06
IEC protection class	II
Luminous efficacy	do 115 lm/W
Luminous flux	1440 - 3200 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0,9
Colour consistency in McAdam ellipses	≤ 3
Mounting type	3 phase rail


Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	77 mm
Beam angle	60/36
LED type	COB - BRIDGELUX
LED quantity	1
Lifespan	50 000 h
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	5÷40
For indoor use	Inside
Length	167
Width	152
Height	247
Colour	Black
Material (housing)	Aluminium
Material (cover)	clear glass



LED line PRIME Code: 210486 EAN: 5905378210486

Track light LUMICANTO 14-29W CCT 36/60° black PRIME

Technical drawing



Light distribution


Additional product photos









Logistics data







Single packaging

Width	85 mm
Height	257 mm
Length	186 mm
Weight	0,58 kg

Bulk packaging

Quantity	20
Width	385 mm
Height	150 mm
Length	530 mm
Volume	0,030 m3
Weight	15,5 kg

Europallet

Height	1590 mm
Quantity in layer	320
Number of layers	3
Bulk quantity	960
Weight	777,6 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 210486 EAN: 5905378210486

Track light LUMICANTO 14-29W CCT 36/60° black PRIME

Example application