

LED line PRIME

Symbol: 210493

EAN: 5905378210493

**Track light LUMICANTO 6-20W CCT  
36/60° black PRIME**



**Dane techniczne**

Parametr	Wartość
Luminous efficacy	do 110 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	620-2000 lm
Colour consistency in McAdam ellipses	≤3
IP protection rating	IP20
Warranty (years)	5
Survival factor	0,9
Lifetime L70B50	50 000
Mounting type	3 phase rail
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	90
Colour	Black
The lumen maintenance factor	96 %
Lamp's diameter	100
Beam angle	60/36 °
Material (cover)	clear glass

Parametr	Wartość
Material (housing)	aluminum
LED type	COB-Bridgelux
LED quantity	1
Power Factor	>0,7
Number of on/off cycles	25000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	5÷40 °C
For indoor use	Inside
IEC protection class	II
IK protection rating	06
Full box quantity	20 pc
Width	152 mm
Height	165 mm
Power	<ul style="list-style-type: none"> <li>• 6-20 W</li> </ul>
Voltage	<ul style="list-style-type: none"> <li>• 220-240 V AC</li> </ul>
Correlated colour temperature	<ul style="list-style-type: none"> <li>• 3000 K</li> <li>• 4000 K</li> <li>• 6000 K</li> </ul>

LED line PRIME

Symbol: 210493


EAN: 5905378210493

**Track light LUMICANTO 6-20W CCT  
36/60° black PRIME**




**Wymiary**

**Rozsył światła**

**Dodatkowe zdjęcia produktowe**



**Wysyłka**



**Opakowanie jednostkowe**

Width	108 mm
Height	175 mm mm
Length	186 mm mm
Weight	0,67 kg kg

**Opakowanie zbiorcze**

Number of pieces/tape in meters pack zb	20 szt.
Width	565 mm mm
Height of collective packaging	365 mm
Length	385 mm mm
Weight	18,4 kg kg
Volume	0,079 m3 m3

**Europaleta**

Quantity collective euro pallet	400 szt.
Weight of a euro pallet	368 kg
Pallet height	1825 mm
Quantity in 1 layer	80 szt.
Number of layers	5

---

LED line PRIME

Symbol: 210493

EAN: 5905378210493

**Track light LUMICANTO 6-20W CCT  
36/60° black PRIME**

---

**Przykładowa realizacja**