

LED line PRIME Code: 211049 EAN: 5905378211049

## LED strip 320 COB 24V 4000K 5W IP20 8mm 5m 500lm/m PRIME



LED 320 COB 24V 4000K 5W PRIME LED line PRIME is an innovative product with a light efficiency of 100 lm/W, providing bright and natural white light with a colour temperature of 4000 K. Thanks to the use of COB technology, it offers excellent lighting quality without flickering effect and high Ra colour reproduction coefficient of 90. This affects visual comfort and interior aesthetics.















#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 5 W / m
Voltage	• 24 V DC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	90
IP protection rating	IP20
IEC protection class	III
Cutting section	5 cm
Luminous efficacy	100
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	<b>≤</b> 3
Wire length	200 mm


Parameter	Value
Luminous flux (1m)	500
Current (1m)	0,20
Beam angle	180
LED type	COB
LED quantity	1600
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (Im)	320
Type of adhesive tape	3M 300 LSE
Ambient temperature suitable for operation	-30÷45
For indoor use	Inside
Length	5000
Width	8
Height	2
Lifetime L80 B*	35000 h




LED line PRIME Code: 211049 EAN: 5905378211049

## LED strip 320 COB 24V 4000K 5W IP20 8mm 5m 500lm/m PRIME

## **Technical drawing**



## **Light distribution**




## Additional product photos








## Logistics data






#### Single packaging

Quantity	5 m
Weight	0,1385 kg



## **Bulk packaging**

Quantity	40
Width	320 mm
Height	180 mm
Length	360 mm
Weight	5,54 kg



#### **Europallet**

2400
1,90 m
60
357 kg

## MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 211049 EAN: 5905378211049

# LED strip 320 COB 24V 4000K 5W IP20 8mm 5m 500lm/m PRIME

**Example application**