

LED line PRIME

Code: 211056

EAN: 5905378211056

**LED strip 320 COB 24V 6500K 5W IP20
8mm 5m 500lm/m PRIME**
A
G
F

The LED 320 COB 24V 6500K 5W PRIME is an innovative lighting solution that is characterized by the highest quality of production and effective light performance of 100 lm/W. Thanks to the color of the light 6500 K, perfect colour reproduction has been achieved, making it ideal for various interior applications. The product shall ensure uniform light distribution at a glowing angle of 180°.






**Technical data**

Parameter	Value	Parameter	Value
Energy efficiency class 2019/2015	F	Wire length	200 mm
Warranty	5	Luminous flux (lm)	500
Power	• 5 W / m	Current (lm)	0,20
Voltage	• 24 V DC	Beam angle	180
Correlated colour temperature	• 6500 K	LED quantity	1600
Colour of the light	White	Compatible dimmer type	PWM
Colour rendering index Ra	90	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	2
IEC protection class	III	LED quantity (lm)	320
Cutting section	5 cm	Type of adhesive tape	3M 300 LSE
Luminous efficacy	100	Ambient temperature suitable for operation	-30 ÷ 45
The lumen maintenance factor	96	For indoor use	Inside
Lifetime L70B50	50 000 h	Length	5000
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h	Width	8
Survival factor	0.9	Height	2
Dimmable function	PWM	Weight	0,085 kg
Colour consistency in McAdam ellipses	≤3		

LED line PRIME

Code: 211056

EAN: 5905378211056

**LED strip 320 COB 24V 6500K 5W IP20
8mm 5m 500lm/m PRIME****Technical drawing****Light distribution****Additional product photos****Logistics data****Single packaging**

Quantity	5 m
Weight	0,114 kg

Bulk packaging

Quantity	40
Width	320 mm
Height	180 mm
Length	360 mm
Weight	5,54 kg

Europallet

MORE EFFICIENCY FOR THE LED WORLD

LED line

LED line PRIME

Code: 211056

EAN: 5905378211056

**LED strip 320 COB 24V 6500K 5W IP20
8mm 5m 500lm/m PRIME**

Example application