

LED line LITE Code: 240621 EAN: 5901583240621

LED bulb GU10 2700K 5,5W 500lm 230V 60° DIM Glass LITE





LITE GU10 5,5W 2700K LED line bulb is an efficient source of warm-colour light that emits 500 lumens. Its colour temperature is 2700 K, which provides a cozy atmosphere. Powered by 220-240 V AC voltage and 50/60 Hz frequency, it has a high energy efficiency of 91 lm/W and a durability of up to 30,000 hours. Thanks to the TRIAC function, it is possible to dim it comfortably.









Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 5.5 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	91
Luminous flux	500 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	Triac
Colour of the light Colour rendering index Ra Luminous efficacy Luminous flux The lumen maintenance factor Lifetime L70B50 Survival factor	White 80 91 500 lm 96 30 000 h


Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	50 mm
Beam angle	60°
LED type	SMD2835
Compatible dimmer type	TRIAC
Power Factor	0,8
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	54
Material (housing)	Glass




LED line LITE Code: 240621 EAN: 5901583240621

LED bulb GU10 2700K 5,5W 500lm 230V 60° DIM Glass LITE

Technical drawing



Light distribution



Additional product photos

Logistics data

Single packaging


Quantity


Width

Height

Length

Weight





10

50 mm


50 mm

60 mm

0,08 kg

Bulk packaging





Europallet

Quantity	4400
Height	1,90 m
Quantity in layer	1600
Number of layers	3
Bulk quantity	44
Weight	390 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 240621 EAN: 5901583240621

LED bulb GU10 2700K 5,5W 500lm 230V 60° DIM Glass LITE

Example application