

LED line LITE

Code: 247804

EAN: 5901583247804

**LED bulb MR16 2700K 3W 273lm 10-14V
AC/DC 36° GU5,3 Glass LITE**



LED line bulb LITE MR16 3W with warm light color 2700K emits a light stream of 273 lumens, which provides a cozy atmosphere. Powered by a voltage of 10-14V AC/DC, it has a light output of 91 lm/W and a long service life of up to 30,000 hours. Thanks to a light angle of 36°, it is ideal as point accent lighting. SMD2835 Diodes guarantee stability and lack of flickering effect, eliminating eye fatigue.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 3 W
Voltage	• 10-14 V AC/DC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	91
Luminous flux	273 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	36°
LED type	SMD2835
Power Factor	0,4
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	50
Fixture's diameter	50 mm
Material (housing)	Glass


LED line LITE

Code: 247804


EAN: 5901583247804

**LED bulb MR16 2700K 3W 273lm 10-14V
AC/DC 36° GU5,3 Glass LITE**

Technical drawing






Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	10
Width	40 mm
Height	40 mm
Length	104 mm
Weight	0,06 kg

Bulk packaging

Quantity	100
Width	290 mm
Height	170 mm
Length	595 mm
Volume	0,029 m3
Weight	6,5 kg
Comments	

Europallet

Quantity	4500
Height	1870 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	286 kg

LED line LITE

Code: 247804

EAN: 5901583247804

**LED bulb MR16 2700K 3W 273lm 10-14V
AC/DC 36° GU5,3 Glass LITE**

Example application