MORE EFFICIENCY FOR THE LED WORLD

LE**D** line

LED line LITE

LED bulb MR16 2700K 3W 273lm 10-14V AC/DC 36° GU5,3 Glass LITE



Code: 247804

EAN: 5901583247804

Â G F

LED line bulb LITE MRI6 3W with warm light color 2700K emits a light stream of 273 lumens, which provides a cozy atmosphere. Powered by a voltage of 10-14V AC/DC, it has a light output of 91 Im/W and a long service life of up to 30,000 hours. Thanks to a light angle of 36°, it is ideal as point accent lighting. SMD2835 Diodes guarantee stability and lack of flickering effect, eliminating eye fatigue.

3 WARRANTY	IP 20	ON/OFF 0 50.000
WARRANTY		00.000

CE

Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Energy class	A++
Warranty	3
Power	• 3 W
Voltage	• 10-14 V AC/DC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	91
Luminous flux	273 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	50 mm
Beam angle	36°
LED type	SMD2835
Power Factor	0,4
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	50
Material (housing)	Glass

MORE EFFICIENCY FOR THE LED WORLD




LED line LITE

Code: 247804


EAN: 5901583247804

LED bulb MR16 2700K 3W 273lm 10-14V AC/DC 36° GU5,3 Glass LITE

Technical drawing




Light distribution




Additional product photos

Logistics data




Single packaging

Quantity	10
Width	40 mm
Height	40 mm
Length	104 mm
Weight	0,06 kg



Bulk packaging

Quantity	100
Width	290 mm
Height	170 mm
Length	595 mm
Volume	0,029 m3
Weight	6,5 kg
Comments	



Europallet

Quantity	4500
Height	1870 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	286 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE

Code: 247804

EAN: 5901583247804

LED bulb MR16 2700K 3W 273Im 10-14V AC/DC 36° GU5,3 Glass LITE

Example application