

LED line LITE

Code: 248948

EAN: 5901583248948

LED line® GU10 5,5W 2200-3000K
345lm 220-240V



LED line bulb GU10 5.5W is a unique light source, which is characterized by a wide range of colour temperature from 2200 K to 3000 K. Thanks to a light stream of 345 lumens and 60° light angle, it provides even interior lighting. High quality of performance guarantees a durability of as much as 30,000 hours and the possibility to carry out up to 50,000 cycles of on- and off-mode.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	63
Colour of the light	White
Energy efficiency class 2019/2015	G
Luminous flux	345
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	90
The lumen maintenance factor	96
Fixture's diameter	50 mm
Beam angle	60

Parameter	Value
Material (housing)	Glass
LED type	SMD2835
Not dimmable	TAK
Compatible dimmer type	TRIAC
Power Factor	0,7
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Full box quantity	100
Lamp's warm-up time to 60%	1 s
Height	54
Energy class	A+
Correlated colour temperature	• 2200-3000 K
Power	• 5.5 W

LED line LITE

Code: 248948


EAN: 5901583248948

LED line® GU10 5,5W 2200-3000K
345lm 220-240V


Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	10
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,08 kg

Bulk packaging

Quantity	100
Width	540 mm
Height	165 mm
Length	280 mm
Volume	0,024 m3
Weight	6 kg
Comments	

Europallet

Quantity	4000
Height	1815 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	264 kg

LED line LITE

Code: 248948

EAN: 5901583248948

**LED line® GU10 5,5W 2200-3000K
345lm 220-240V**

Example application