

LED line PRIME Code: 478245 EAN: 5907777478245

LED strip 480 COB 24V 2700K 18W IP20 10mm 5m 1800lm/m PRIME



LED 480 COB 24V 2700K 18W LED line PRIME is an excellent lighting solution that stands out for high quality COB diodes. It emits a warm, white light with a colour temperature of 2700K, ideal for creating a cozy atmosphere. With a power of 18W per metre and a light stream of 1800 lumens, the tape provides excellent energy efficiency. Its length is 5 metres and has a flexibility of assembly.















Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 18 W / m
Voltage	• 24 V DC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	90
IP protection rating	IP20
IEC protection class	III
Cutting section	5 cm
Luminous efficacy	80
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 \approx 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤3


Parameter	Value
Wire length	200 mm
Luminous flux (1m)	1800
Current (lm)	0,5
Beam angle	180
LED type	COB
LED quantity	2400
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	480
Type of adhesive tape	3M 300 LSE
Ambient temperature suitable for operation	-30÷45
For indoor use	Inside
Length	5000
Width	10
Height	2
Weight	0,119 kg




LED line PRIME Code: 478245 EAN: 5907777478245

LED strip 480 COB 24V 2700K 18W IP20 10mm 5m 1800lm/m PRIME

Technical drawing



Light distribution



Additional product photos

Logistics data

Single packaging

Quantity


Width


Height

Length

Weight

Comments





5 m


153 mm

15 mm

153 mm

0,148 kg





Europallet

Quantity	2400
Height	1,90 m
Quantity in layer	240
Number of layers	10
Bulk quantity	60
Weight	392 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 478245 EAN: 5907777478245

LED strip 480 COB 24V 2700K 18W IP20 10mm 5m 1800lm/m PRIME

Example application