

LED line PRIME Code: 479785 EAN: 5907777479785

LED strip 480 COB 24V 2700K 11W IP20 8mm 5m 1100lm/m PRIME



LED LED line PRIME 480 COB 24V 2700K 11W is a modern lighting solution that provides high quality light with a warm colour of 2700K. Thanks to COB technology, the tape is characterized by a light output of 100 lm/W and an evenly distributed izzface at an angle of 180°. The product reaches a total luminous flux of 1100 lm per metre.















Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 11 W / m
Voltage	• 24 V DC
Colour of the light	White
Colour rendering index Ra	90
IP protection rating	IP20
IEC protection class	III
Cutting section	5 cm
Luminous efficacy	100
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤ 3
Wire length	200 mm


Parameter	Value
Luminous flux (1m)	1100
Current (1m)	0,46
Beam angle	180
LED type	COB
LED quantity	2400
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	480
Type of adhesive tape	3M 300 LSE
Ambient temperature suitable for operation	-30÷45
For indoor use	Inside
Length	5000
Width	8
Height	2
Lifetime L80 B*	35000 h




LED line PRIME Code: 479785 EAN: 5907777479785

LED strip 480 COB 24V 2700K 11W IP20 8mm 5m 1100lm/m PRIME

Technical drawing



Light distribution



Additional product photos

Logistics data

Single packaging

Quantity


Width


Height

Length

Weight


Comments






Bulk packaging





Quantity	40
Width	320 mm
Height	180 mm
Length	360 mm
Volume	0,020 m3
Weight	5,87 kg
Comments	



Europallet

Quantity	2400
Height	1,90 m
Quantity in layer	240
Number of layers	10
Bulk quantity	60
Weight	377 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 479785 EAN: 5907777479785

LED strip 480 COB 24V 2700K 11W IP20 8mm 5m 1100lm/m PRIME

Example application