

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LED line LITE

**Supplier's address:** LEDIN Group Sp. z o.o., Dębowa 1, 07-410 Rzekuń Tobolice Mazowieckie, PL

**Model identifier:** 240621

**Type of light source:**

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	GU10		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers


## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G
Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	390 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power ( $P_{\text{on}}$ ), expressed in W	5,5	Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,463 0,418	
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	433	Beam angle in degrees, or the range of beam angles that can be set	60	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	9	Survival factor	0,90	
the lumen maintenance factor	0,96			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,80	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,6	

(a) '-': not applicable;

(b) '-': not applicable;



Model placed on the Union market from 07/11/2024



**EPREL registration number:** 2277418

<https://eprel.ec.europa.eu/qr/2277418>

**Supplier:** LEDIN GROUP SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ (Manufacturer)

**Website:** [www.ledin.pl](http://www.ledin.pl)

**Customer care service:**

**Name:** LEDIN Group Sp. z o.o.

**Website:** [www.ledin.pl](http://www.ledin.pl)

**Email:** [kontakt@ledin.pl](mailto:kontakt@ledin.pl)

**Phone:** +48297647700

**Address:**

Dębowa 1  
07-410 Tobolice  
Poland